











Headlighting







Portfolio

Xenon

					
	D1S	D1 NBV	D2S	D2S NBV	D2R
Type Nr.	85410	85415 NBV	85122	85122 NBV	85126
Voltage	85V	85V	85V	85V	85V
Power	35W	35W	35W	35W	35W
Lumen output	3,200 lm	3,200 lm	3,400 lm	3,400 lm	2,800 lm
Lifetime B3	2,000 h	2,000 h	1,500 h	1,500 h	1,500 h
Lifetime Tc	3,000 h	3,000 h	2,500 h	2,500 h	2,500 h
Regulations	R99/DOT	R99/DOT	R99/DOT	R99/DOT	R99/DOT

					
	D3S	D3 NBV	D4S	D4R	D5S
Type Nr.	42302	42403 NBV	42402	42406	12410
Voltage	42V	42V	42V	42V	12V
Power	35W	35W	35W	35W	25W
Lumen output	3,200 lm	3,200 lm	3,200 lm	2,800 lm	2,000 lm
Lifetime B3	2,000 h	2,000 h	2,000 h	2,000 h	2,500 h
Lifetime Tc	3,000 h	3,000 h	3,000 h	3,000 h	4,000 h
Regulations	R99/DOT	R99/DOT	R99/DOT	R99/DOT	R99/DOT

Halogen

						
	H4 LL	H4 HPLL	H4 HP+	H4 BV+	H7	H7 LL
Type Nr.	12342 LL	12342 HPLL	12342 HP+	12342 BV+	12972	12972 LL
Voltage*	13.2V	13.2V	13.2V	13.2V	13.2V	13.2V
Power	60/55W	60/55W	60/55W	60/55W	55W	55W
Lumen output	1,650/1,000 lm	1,650/1,000 lm	1,750/1,100 lm	1,650/1,000 lm	1,500 lm	1,500 lm
Lifetime B3	900 h	2,000 h	400 h	200 h	330 h	700 h
Lifetime Tc	1,500 h	3,000 h	700 h	400 h	550 h	1,100 h
Regulations	R37	R37	R37	R37	R37/DOT	R37/DOT

*Test voltage

Headlighting

Portfolio

Halogen



	H7 HPLL	H7 EL	H7 BV+**	H8 LL	H8 BV+	H9	H9 BV+
Type Nr.	12972 HPLL	12972 EL	12972 BV+	12360	12360 BV+	12361	12361 BV+
Voltage*	13.2V	13.2V	13.2V	13.2V	13.2V	13.2V	13.2V
Power	55W	55W	55W	35W	35W	65W	65W
Lumen output	1,500 lm	1,500 lm	1,500 lm	800 lm	800 lm	2,100 lm	2,100 lm
Lifetime B3	1,000 h	600 h	200 h	800 h	200 h	270 h	200 h
Lifetime Tc	1,500 h	950 h	350 h	1,500 h	400 h	540 h	400 h
Regulations	R37/DOT	R37/DOT	R37/DOT	R37/DOT	R37/DOT	R37/DOT	R37/DOT

*Test voltage

**Also available with blue top coating



	H11 LL	H11 BV+	H18 LL	H19 LL	HIR2	HIR2 LL
Type Nr.	12362 LL	12362 BV+	12643 LL	12644 LL	9012	9012 LL
Voltage*	13.2V	13.2V	13.2V	13.2V	13.2V	13.2V
Power	55W	55W	65W	60/55W	55W	55W
Lumen output	1,350 lm	1,350 lm	1,700 lm	1,750/1,200 lm	1,875 lm	1,875 lm
Lifetime B3	1,000 h	200 h	700 h	900 h	500 h	900 h
Lifetime Tc	2,000 h	350 h	1,100 h	1,500 h	900 h	1,400 h
Regulations	R37/DOT	R37/DOT	R37/DOT	R37/DOT	R37/DOT	R37/DOT

*Test voltage



	PSX24W	PSX26W
Type Nr.	12276	12278
Voltage*	13.2V	13.2V
Power	23.5W	23.5W
Lumen output	465 lm	465 lm
Lifetime B3	1,000 h	1,000 h
Lifetime Tc	2,000 h	2,000 h
Regulations	R37	R37

*Test voltage

©2016 Lumileds Holding B.V. All rights reserved.
LUXEON is a registered trademark of the Lumileds Holding B.V.
in the United States and other countries.

www.lumileds.com

Neither Lumileds Holding B.V. nor its affiliates shall be liable for any kind of loss of data or any other damages, direct, indirect or consequential, resulting from the use of the provided information and data. Although Lumileds Holding B.V. and/or its affiliates have attempted to provide the most accurate information and data, the materials and services information and data are provided "as is," and neither Lumileds Holding B.V. nor its affiliates warrants or guarantees the contents and correctness of the provided information and data. Lumileds Holding B.V. and its affiliates reserve the right to make changes without notice. You as user agree to this disclaimer and user agreement with the download or use of the provided materials, information and data.