





LED front lighting

Portfolio




Part name	Part number	CCT / wavelength	LED color	Flux @ bin		Binning condition Tc	Max. DC If	Forward voltage	Max. Tj	Typ rth J-C
				Min	Max					
LUXEON Altilon H1K PnP 1x4	LAPH-M46-XXX	5,500 - 6,250 K		1,107 lm	1,298 lm	85°C	1,000 mA	12.4V	150°C	1.3°C/W
LUXEON Altilon H1K PnP 1x5	LAPH-M56-XXX	5,500 - 6,250 K		1,412 lm	1,603 lm	85°C	1,000 mA	15.5V	150°C	1.1°C/W
LUXEON Altilon SMD 1x2	A1SB-58502DH0	5,180 - 6,250 K		560 lm	620 lm	85°C	1,000 mA	6.0V	150°C	2.3°C/W
LUXEON Altilon SMD 1x3	A1SB-58503DH0	5,180 - 6,250 K		840 lm	930 lm	85°C	1,000 mA	9.0V	150°C	1.8°C/W
LUXEON Altilon SMD 1x4	A1SB-58504DH0	5,180 - 6,250 K		920 lm	1,040 lm	85°C	1,000 mA	12.0V	150°C	1.5°C/W
LUXEON Altilon SMD 1x5	A1SB-58505DH0	5,180 - 6,250 K		1,400 lm	1,550 lm	85°C	1,000 mA	15.0V	150°C	1.2°C/W
LUXEON Neo 1mm²	A1N1-58501DH0	5,180 - 6,250 K		280 lm	310 lm	85°C	1,000 mA	3.0V	150°C	2°C/W
LUXEON Neo 0.5mm²	A1N1-58500BH0	5,180 - 6,250 K		125 lm	140 lm	85°C	500 mA	3.0V	150°C	4.1°C/W
LUXEON F CW	LFMH-C1A	5,180 - 6,250 K		90 lm	110 lm	85°C	350 mA	2.77V	150°C	4°C/W
LUXEON F ES CW	LFXH-C2B	5,500 - 6,680 K		220 lm	240 lm	85°C	700 mA	2.82V	150°C	3°C/W
LUXEON F Plus CW	LFMH-C1C	5,500 - 6,250 K		247 lm	299 lm	85°C	1,000 mA	2.94V	150°C	4°C/W
LUXEON FX Plus CW	A1FX-5850	5,500 - 6,250 K		270 lm	290 lm	85°C	1,000 mA	2.94V	150°C	3.5°C/W
LUXEON F PC Amber	LFMH-L1A	588 - 592 nm		70 lm	90 lm	85°C	350 mA	2.78V	135°C	4°C/W
LUXEON F Plus PC Amber	LFMH-L1C	588 - 592 nm		164 lm	196 lm	85°C	1,000 mA	2.98V	135°C	5°C/W
LUXEON FX Plus PC Amber	A1FX-0591	588 - 592 nm		170 lm	200 lm	85°C	1,000 mA	2.78V	150°C	3.8°C/W
LUXEON Versat 3030 CW 150	A1VA-5850A010	5,500 - 6,250 K		53 lm	70 lm	25°C	150 mA	3.10V	150°C	13°C/W
LUXEON Versat 3030 PCA 150	A1VA-P591A010	588 - 592 nm		30 lm	48 lm	25°C	150 mA	3.10V	150°C	16°C/W
LUXEON Rebel	LXMA-PW01	5,000 - 6,300 K		110 lm	150 lm	25°C	350 mA	2.92V	150°C	10°C/W
LUXEON Rebel PC Amber	LXMA-PL02	588 - 592 nm		90 lm	130 lm	25°C	350 mA	2.92V	135°C	10°C/W
LUXEON Rebel Red Orange	LXMA-PH03	612 - 618 nm		80 lm	110 lm	25°C	350 mA	2.10V	150°C	8°C/W

All specifications are based on MP.

LED rear lighting

Portfolio



Part name	Part number	CCT / wavelength	LED color	Flux @ bin		Binning condition		Max. DC If	Forward voltage	Max. TJ	Typ rth J-C
				Min	Max	Tc	If				
LUXEON Versat 3030 Red Orange 200	A1VA-O612A10	612 - 618 nm		30 lm	52 lm	25°C	200 mA	300 mA	2.60V	150°C	15°C/W
LUXEON Versat 3030 Red Orange 700	A1VA-O612C10	612 - 618 nm		130 lm	224 lm	25°C	700 mA	1 A	2.60V	150°C	5°C/W
LUXEON Versat 3030 Super Red 200 (630 nm)	A1VA-S627A10	627 - 632 nm		18 lm	30 lm	25°C	200 mA	300 mA	2.60V	150°C	15°C/W
LUXEON Versat 3030 Super Red 700 (630 nm)	A1VA-S627C10	627 - 632 nm		75 lm	130 lm	25°C	700 mA	1 A	2.60V	150°C	5°C/W
SignalSure 30 Amber	A1DT-A588L	588 - 595 nm		2.1 lm	3.6 lm	25°C	30 mA	60 mA	2.55V	125°C	100°C/W
SignalSure 75 Amber	A1DP-A588L	588 - 595 nm		7.3 lm	12.5 lm	25°C	75 mA	90 mA	2.67V	135°C	45°C/W
SignalSure 150 Amber	A1DE-A588L	588 - 595 nm		12.5 lm	21.0 lm	25°C	150 mA	200 mA	2.79V	135°C	45°C/W
SignalSure 250 Amber	A1DL-A588L	627 - 632 nm		25.0 lm	52.0 lm	25°C	250 mA	300 mA	2.79V	135°C	25°C/W
SignalSure 30 Red Orange	A1DT-O612L	612 - 618 nm		3.6 lm	6.1 lm	25°C	30 mA	60 mA	3.6V	125°C	100°C/W
SignalSure 75 Red Orange	A1DP-O612L	612 - 618 nm		10.4 lm	18.0 lm	25°C	75 mA	90 mA	2.55V	135°C	45°C/W
SignalSure 150 Red Orange	A1DE-O612L	612 - 618 nm		21.0 lm	36.0 lm	25°C	150 mA	200 mA	2.79V	135°C	45°C/W
SignalSure 250 Red Orange	A1DL-O612L	612 - 618 nm		36.0 lm	62.0 lm	25°C	250 mA	300 mA	2.79V	135°C	25°C/W
SignalSure 30 Super Red	A1DT-S627L	627 - 638 nm		2.1 lm	3.6 lm	25°C	30 mA	60 mA	2.45V	125°C	100°C/W
SignalSure 75 Super Red	A1DP-S627L	627 - 638 nm		6.1 lm	10.4 lm	25°C	75 mA	90 mA	2.79V	135°C	45°C/W
SignalSure 150 Super Red	A1DE-S627L	627 - 632 nm		12.5 lm	21.0 lm	25°C	150 mA	200 mA	2.79V	135°C	45°C/W
SignalSure 250 Super Red	A1DL-S627L	627 - 632 nm		21.0 lm	43.0 lm	25°C	250 mA	300 mA	2.79V	135°C	25°C/W
SnapLED 75 Amber	SSL075-A588	588 - 595 nm		7.3 lm	12.5 lm	25°C	75 mA	75 mA	2.67V	135°C	30°C/W
SnapLED 150 Amber	SSL150-A588	588 - 595 nm		12.5 lm	21.0 lm	25°C	150 mA	150 mA	2.79V	135°C	30°C/W
SnapLED 75 Red Orange	SSL075-O612	613 - 628 nm		10.4 lm	18.0 lm	25°C	75 mA	75 mA	2.67V	135°C	30°C/W
SnapLED 150 Red Orange	A1SS-O612	612 - 618 nm		21.0 lm	36.0 lm	25°C	150 mA	200 mA	2.79V	135°C	30°C/W
SnapLED Xtreme Amber	A1SX-A588	588 - 595 nm		30.0 lm	62.0 lm	25°C	300 mA	350 mA	2.91V	150°C	15°C/W
SnapLED Xtreme Red Orange	A1SX-O612	612 - 618 nm		43.0 lm	75.0 lm	25°C	300 mA	350 mA	2.91V	150°C	15°C/W
SnapLED Xtreme Super Red	A1SX-S627	632 - 632 nm		25.0 lm	52.0 lm	25°C	300 mA	350 mA	2.91V	150°C	15°C/W

All specifications are based on MP.

©2017 Lumileds Holding B.V. All rights reserved.
LUXEON is a registered trademark of the Lumileds Holding B.V.
in the United States and other countries.

www.lumileds.com

Neither Lumileds Holding B.V. nor its affiliates shall be liable for any kind of loss of data or any other damages, direct, indirect or consequential, resulting from the use of the provided information and data. Although Lumileds Holding B.V. and/or its affiliates have attempted to provide the most accurate information and data, the materials and services information and data are provided "as is," and neither Lumileds Holding B.V. nor its affiliates warrants or guarantees the contents and correctness of the provided information and data. Lumileds Holding B.V. and its affiliates reserve the right to make changes without notice. You as user agree to this disclaimer and user agreement with the download or use of the provided materials, information and data.